

# Primalex Project

## BENEFITS:

EXTRA HIGH WHITENESS ~ 92% BaSO<sub>4</sub>  
PERFECT COVERAGE  
HIGHLY RESISTANT TO ABRASION  
MATT

PACKAGING: 7+1 kg, 18 kg

## PRODUCT DESCRIPTION:

Primalex Project is a paint made to fit the particular needs of professional painters, accustomed to using high-quality paints. When it comes to the key parameters, the paint delivers. Project has extra high whiteness (~92% BaSO<sub>4</sub>), it has perfect covering abilities, and easy application. All these characteristics are the key, the guarantee for the perfect results and spotless interior's outlook. Further more, due to paint's very high vapour permeation ability, it can be used for sanitation painting also.

## USAGE/PRIMALEX TIPS:

This paint is perhaps best suited for living rooms, offices, places of business, corridors and other places, that put high demands on quality.

## APPLICATION:

Before painting, the wall must be cleaned and degreased by a soap-based solution. New or redone plasters needs to be at least 4 weeks let to dry properly. In case the older painting is too thick, it should be scraped down. Older paint in thinner layers and walls scraped down or bare, properly penetrate with Primalex Deep Penetration or Primalex Universal Penetration by its manual. Thin Primalex Project by the below table and after thorough stir, paint is ready to use. Apply by plush paintroller, paintbrush or spray. When painting less firm surfaces, do not retrace the roller back, wet paint could be torn down again. Usually, this paint has better effects when applied in 2 layers. During the painting, we recommend to stir the paint from time to time. Spilled drops and equipment should be cleansed before the paint dries up. Primalex Project can be coloured by the Primalex tone colours palette.

## THINNING:

1<sup>st</sup> layer: max. 20% watering down, that is max 0.2 l on 1 kg of paint.

2<sup>nd</sup> layer: max 10%, that is 0.1 l on 1 kg of paint.

## SPREADING RATE:

	8 kg	18 kg
<b>One-layer spreading rate (m<sup>2</sup>/l)*</b> 2-Layer application is suggested	48 – 80 m <sup>2</sup>	108 – 180 m <sup>2</sup>

## TECHNICAL DESCRIPTION:

Parameter	Value
Dried-up whiteness (% BaSO <sub>4</sub> )	Min. 92
Density (kg/l)	1.66 kg/l
Dry paint's abrasion resistance (grade)	0.5

Content of volatile substances (%)	Max. 38
85° Gloss	< 8.0
Adhesion to concrete (MPa)	0.25
Equivalent diffusion thickness $s_d$ - max	0.07

### HEALTH, SAFETY & ENVIRONMENTAL INFORMATION:

When handling the product, do not eat, drink or smoke. When applying it is advisable to wear eye protection with side-panels. Also, ventilate the room. When spraying, do not breathe spray. When spraying, wear protective equipment. If swallowed, rinse mouth with water (only if the person is conscious). In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. In case of accident or if you feel unwell seek medical advice immediately. After cleaning the skin, apply regenerative lotion.

**P101** If medical advice is needed, have product container or label at hand

**P102** Keep out of reach of children

Safety data sheet available on request.

NOT EDIBLE, MUST NOT FREEZE! STORE IN TEMPERATURE RANGE 40-95° F.

Caution, the 18 kg packing must be handled as a freight.

Originally sealed and properly stored product keeps its properties at least up to the date on the cover. After the unused paint dries up, it is possible to dispose of it in regular garbage. The packing is fully recyclable. Packing unclean of dangerous substances or stained by them please turn over to junkyard specified for that purpose by local authorities.

**Leftovers:** Assigned as non-hazardous waste code **O 08 01 12** waste paint and varnish other than those mentioned in 08 01 11.

**Clean packing:** **O 15 01 06** Miscellaneous packaging.

### VOC:

A/a, content's max volume of VOS's is 30 g/l (2010); this product contains max 2 g/l VOC when ready to use.

### CONTACT INFORMATION:

PPG Deco Czech a.s.

CZ- Břasy č.p.223; PSČ 338 24

Czech Republic

primalexcz@ppg.com

Infoline: 800 100 752

[www.primalex.cz](http://www.primalex.cz)

Applying pictograms: Brush, Paintroller, Spraygun

Disposal pictograms: 05,PP triangle; green punkt